










A process for improving the properties of ground recycled rubber**Publication number:** EP0937742**Publication date:** 1999-08-25**Inventor:** WIDEMAN LAWSON GIBSON (US); BALOGH
GEORGE FRANK (US); MCQUATE RAYMOND DEAN
(US)**Applicant:** GOODYEAR TIRE & RUBBER (US)**Classification:****- International:** *B29C35/02; C08J11/04; C08K5/36; C08K5/372;
C08L21/00; B29K21/00; B29K105/24; B29C35/02;
C08J11/00; C08K5/00; C08L21/00; (IPC1-7):
C08J11/04; C08L21/00***- European:** C08K5/372; C08L21/00**Application number:** EP19990102966 19990215**Priority number(s):** US19980027312 19980220**Also published as:** US5883139 (A1)
 JP11309724 (A)
 CA2260737 (A1)
 EP0937742 (B1)
 DE69919243T (T2)**Cited documents:** EP0744436
 EP0780429
 XP002105181
 JP52105951**Report a data error here**

Abstract not available for EP0937742

Abstract of corresponding document: **US5883139**

A process involving (a) homogeneously dispersing tetrathiodipropionic acid in a recycled rubber having an individual particle size no greater than 420 microns, (b) mixing the treated recycled rubber with unvulcanized rubber and (c) vulcanizing the rubber mixture.

Data supplied from the **esp@cenet** database - Worldwide